

**Pulegge per cinghie dentate passo metrico ST per cinghie "AT"**  
**ST Timing belt pulleys metric pitch for "AT" belts**  
**ST Zahnriemenscheiben metrische Teilung für "AT" riemen**  
**Poulies dentées ST pour courroies "AT" pas métrique**  
**Poleas dentadas ST para correas "AT" con paso metrico**

**Materiale:**  
**alluminio 6082 T6**  
**UNI 9006/4 adatto al**  
**trattamento anodico**



**Material:**  
**aluminium 6082 T6**  
**UNI 9006/4 suitable for**  
**anodic treatment**

**Werkstoff:**  
**aluminium 6082 T6**  
**UNI 9006/4 geeignet für**  
**anodischen oxydation**

**Matière:**  
**aluminium 6082 T6**  
**UNI 9006/4 apte au**  
**traitement anodique**

**Material:**  
**aluminio 6082 T6**  
**UNI 9006/4 apto para la**  
**oxidacion anodica**

**Tipo / Type**  
**6F**



**Tipo / Type**  
**6**

**ST 5**

(Passo 5 mm)  
 per cinghia larghezza 10 mm

(Pitch 5 mm)  
 for belt width 10 mm

(Teilung 5 mm)  
 für Riemenbreite 10 mm

(Pas 5 mm)  
 pour courroies largeur 10 mm

(Paso 5 mm)  
 para correas ancho 10 mm

Codice Code symbol / Fabriknummer Code symbole / Numero de fabrica	Nostro codice Our code / Unser kode Notre code / Nuestro codigo	Tipo Type / Typ Type / Tipo	Codice flangia Flange code / Bordscheiben-Code Code flasque / Código brida	N. denti N. of teeth / Zahnezahl N. bre de dents / Cantidad de dientes	De	Df	Dm	F	L	d	Peso / Weight Gewicht / Poids / Peso Kg
21 ST5/12-2	21ST512	6F	FL001	12	17,85	23,0	11	15	21	-	0,018
21 ST5/14-2	21ST514	6F	FL002	14	21,05	25,0	13	15	21	-	0,019
21 ST5/15-2	21ST515	6F	FL004	15	22,65	28,0	16	15	21	-	0,021
21 ST5/16-2	21ST516	6F	FL005	16	24,20	32,0	18	15	21	-	0,025
21 ST5/18-2	21ST518	6F	FL006	18	27,40	32,0	20	15	21	-	0,031
21 ST5/19-2	21ST519	6F	FL008	19	29,00	36,0	22	15	21	-	0,036
21 ST5/20-2	21ST520	6F	FL008	20	30,60	36,0	23	15	21	-	0,038
21 ST5/22-2	21ST522	6F	FL009	22	33,85	38,0	24	15	21	-	0,048
21 ST5/24-2	21ST524	6F	FL013	24	37,00	42,0	26	15	21	-	0,054
21 ST5/25-2	21ST525	6F	FL012	25	38,60	44,0	26	15	21	-	0,058
21 ST5/26-2	21ST526	6F	FL012	26	40,20	44,0	26	15	21	-	0,062
21 ST5/27-2	21ST527	6F	FL011	27	41,80	48,0	30	15	21	8	0,064
21 ST5/28-2	21ST528	6F	FL011	28	43,35	48,0	32	15	21	8	0,071
21 ST5/30-2	21ST530	6F	FL016	30	46,55	51,0	34	15	21	8	0,076
21 ST5/32-2	21ST532	6F	FL018	32	49,70	54,0	36	15	21	8	0,088
21 ST5/36-2	21ST536	6F	FL023	36	56,05	64,0	38	15	21	8	0,114
21 ST5/40-2	21ST540	6F	FL024	40	62,45	66,5	40	15	21	8	0,138
21 ST5/42-2	21ST542	6F	FL026	42	65,60	70,0	40	15	21	8	0,180
21 ST5/44-0	21ST544	6	-	44	68,80	-	45	15	21	8	0,185
21 ST5/48-0	21ST548	6	-	48	75,15	-	50	15	21	8	0,200
21 ST5/60-0	21ST560	6	-	60	94,25	-	65	15	21	8	0,307

(Passo 5 mm)  
 per cinghia larghezza 16 mm

(Pitch 5 mm)  
 for belt width 16 mm

(Teilung 5 mm)  
 für Riemenbreite 16 mm

(Pas 5 mm)  
 pour courroies largeur 16 mm

(Paso 5 mm)  
 para correas ancho 16 mm

Codice Code symbol / Fabriknummer Code symbole / Numero de fabrica	Nostro codice Our code / Unser kode Notre code / Nuestro codigo	Tipo Type / Typ Type / Tipo	Codice flangia Flange code / Bordscheiben-Code Code flasque / Código brida	N. denti N. of teeth / Zahnezahl N. bre de dents / Cantidad de dientes	De	Df	Dm	F	L	d	Peso / Weight Gewicht / Poids / Peso Kg
27 ST5/12-2	27ST512	6F	FL001	12	17,85	23,0	11	21	27	-	0,022
27 ST5/14-2	27ST514	6F	FL002	14	21,05	25,0	13	21	27	-	0,026
27 ST5/15-2	27ST515	6F	FL004	15	22,65	28,0	16	21	27	-	0,029
27 ST5/16-2	27ST516	6F	FL005	16	24,20	32,0	18	21	27	-	0,035
27 ST5/18-2	27ST518	6F	FL006	18	27,40	32,0	20	21	27	-	0,043
27 ST5/19-2	27ST519	6F	FL008	19	29,00	36,0	22	21	27	-	0,049
27 ST5/20-2	27ST520	6F	FL008	20	30,60	36,0	23	21	27	-	0,053
27 ST5/22-2	27ST522	6F	FL009	22	33,85	38,0	24	21	27	-	0,054
27 ST5/24-2	27ST524	6F	FL013	24	37,00	42,0	26	21	27	-	0,076
27 ST5/25-2	27ST525	6F	FL012	25	38,60	44,0	26	21	27	-	0,081
27 ST5/26-2	27ST526	6F	FL012	26	40,20	44,0	26	21	27	-	0,085
27 ST5/27-2	27ST527	6F	FL011	27	41,80	48,0	30	21	27	8	0,090
27 ST5/28-2	27ST528	6F	FL011	28	43,35	48,0	32	21	27	8	0,092
27 ST5/30-2	27ST530	6F	FL016	30	46,55	51,0	34	21	27	8	0,105
27 ST5/32-2	27ST532	6F	FL018	32	49,70	54,0	36	21	27	8	0,123
27 ST5/36-2	27ST536	6F	FL023	36	56,05	64,0	38	21	27	8	0,160
27 ST5/40-2	27ST540	6F	FL024	40	62,45	66,5	40	21	27	8	0,193
27 ST5/42-2	27ST542	6F	FL026	42	65,60	70,0	40	21	27	8	0,205
27 ST5/44-0	27ST544	6	-	44	68,80	-	45	21	27	8	0,228
27 ST5/48-0	27ST548	6	-	48	75,15	-	50	21	27	8	0,280
27 ST5/60-0	27ST560	6	-	60	94,25	-	65	21	27	8	0,430

(Passo 5 mm)  
 per cinghia larghezza 25 mm

(Pitch 5 mm)  
 for belt width 25 mm

(Teilung 5 mm)  
 für Riemenbreite 25 mm

(Pas 5 mm)  
 pour courroies largeur 25 mm

(Paso 5 mm)  
 para correas ancho 25 mm

Codice Code symbol / Fabriknummer Code symbole / Numero de fabrica	Nostro codice Our code / Unser kode Notre code / Nuestro codigo	Tipo Type / Typ Type / Tipo	Codice flangia Flange code / Bordscheiben-Code Code flasque / Código brida	N. denti N. of teeth / Zahnezahl N. bre de dents / Cantidad de dientes	De	Df	Dm	F	L	d	Peso / Weight Gewicht / Poids / Peso Kg
36 ST5/12-2	36ST512	6F	FL001	12	17,85	23,0	11	30	36	-	0,031
36 ST5/14-2	36ST514	6F	FL002	14	21,05	25,0	13	30	36	-	0,037
36 ST5/15-2	36ST515	6F	FL004	15	22,65	28,0	16	30	36	-	0,041
36 ST5/16-2	36ST516	6F	FL005	16	24,20	32,0	18	30	36	-	0,050
36 ST5/18-2	36ST518	6F	FL006	18	27,40	32,0	20	30	36	-	0,061
36 ST5/19-2	36ST519	6F	FL008	19	29,00	36,0	22	30	36	-	0,070
36 ST5/20-2	36ST520	6F	FL008	20	30,60	36,0	23	30	36	-	0,076
36 ST5/22-2	36ST522	6F	FL009	22	33,85	38,0	24	30	36	-	0,080
36 ST5/24-2	36ST524	6F	FL013	24	37,00	42,0	26	30	36	-	0,109
36 ST5/25-2	36ST525	6F	FL012	25	38,60	44,0	26	30	36	-	0,118
36 ST5/26-2	36ST526	6F	FL012	26	40,20	44,0	26	30	36	-	0,120
36 ST5/27-2	36ST527	6F	FL011	27	41,80	48,0	30	30	36	8	0,128
36 ST5/28-2	36ST528	6F	FL011	28	43,35	48,0	32	30	36	8	0,135
36 ST5/30-2	36ST530	6F	FL016	30	46,55	51,0	34	30	36	8	0,150
36 ST5/32-2	36ST532	6F	FL018	32	49,70	54,0	36	30	36	8	0,178
36 ST5/36-2	36ST536	6F	FL023	36	56,05	64,0	38	30	36	8	0,230
36 ST5/40-2	36ST540	6F	FL024	40	62,45	66,5	40	30	36	8	0,278
36 ST5/42-2	36ST542	6F	FL026	42	65,60	70,0	40	30	36	8	0,284
36 ST5/44-0	36ST544	6	-	44	68,80	-	45	30	36	8	0,315
36 ST5/48-0	36ST548	6	-	48	75,15	-	50	30	36	8	0,400
36 ST5/60-0	36ST560	6	-	60	94,25	-	65	30	36	8	0,614