

SEMPERIT () LM 1-EPOM 3 . - .

۱_

LM1-EPDM

Food Quality Hose

Application:

_ |

A flexible discharge hose for use in breweries and the food and beverage industries.

Suitable for use with alcohol (max. 40%) and soft drinks, fatty (max. 36%) and non-fatty foods.

Feature:

White EPDM food quality tube with high temperature resistance.

Tasteless, odourless, kink resistant, sturdy, very light.

Standard/approval:

BfR (former BgVV) XXI:2002 (Kat. 2), Weihenstephan, FDA (CFR 21 §177.2600).

Notice:

Very high resistance to many aggressive cleaning agents.

For the application of cleaning agents please see our separate information sheet.

ATTENTION: Not suitable for dry conveyance.

Temperature range:

-35°C / +95°C. Steam cleaning up to max. 130°C / 30 min, unpressurised.

Safety factor:

3.15 : 1

Tube:

EPDM, white, smooth, food quality.

Reinforcement:

Textile wrapped.

Cover:

SBR/NR/EPDM, red, abrasion resistant, ozone and weather resistant, cloth impression.

Marking:

Continuous transfer tape, white: "SEMPERIT S LM1-EPDM Brewer/Kellermeister D PN 12 bar".



| Article number | Internal-Ø in | | Wall width | External-Ø | Work. pressure | Number of inserts | Bending radius | Weight approx. | Coil length |
|----------------|---------------|-------|------------|------------|-------------------|----------------------|-------------------|-------------------|-------------|
| | mm | inch | in mm | in mm | (max.) bar | | (min.) in mm | kg/m | (max.) m |
| 48256 1350 | 13,0 | 1/2 | 5,0 | 23,0 | 12 | 2 | 50 | 0,40 | 40 |
| 48256 1950 | 19,0 | 3/4 | 5,0 | 29,0 | 12 | 2 | 100 | 0,55 | 40 |
| 48256 2560 | 25,0 | 1 | 6,0 | 37,0 | 12 | 2 | 150 | 0,85 | 40 |
| 48256 3280 | 32,0 | 1 1/4 | 8,0 | 48,0 | 12 | 4 | 170 | 1,45 | 40 |
| 48256 3890 | 38,0 | 1 1/2 | 9,0 | 56,0 | 12 | 4 | 200 | 1,85 | 40 |
| 48256 4010 | 40,0 | | 10,0 | 60,0 | 12 | 4 | 250 | 2,25 | 40 |
| 48256 5011 | 50,0 | | 11,0 | 72,0 | 12 | 4 | 350 | 2,95 | 40 |
| 48256 6011 | 60,0 | | 11,0 | 82,0 | 12 | 4 | 420 | 3,55 | 40 |
| 48256 6512 | 65,0 | | 12,0 | 89,0 | 12 | 4 | 450 | 4,05 | 40 |
| 58256 7614 | 76,2 | 3 | 14,4 | 105,0 | 12 | 6 | 600 | 6,00 | 40 |
| 56256 8015 | 80,0 | | 15,0 | 110,0 | 12 | 6 | 650 | 6,40 | 40 |
| 56256 0015 | 100,0 | | 15,0 | 130,0 | 12 | 6 | 750 | 7,75 | 40 |

Please note: Before using our products with new or untested media, or for applications that are not clearly indicated in the product information, written advice must be obtained from a specialist dealer or a Semperit application engineer. For safety reasons, all products must be inspected regularly for operational safety and replaced in the event of any damage (especially of the cover) or unusual signs of wear and tear. All products must be stored, handled and maintained in accordance with all our respective instructions and DIN 7716:1982. The information in our catalogue as well as each individual datasheet is subject to change at any time without notice since we are constantly developing and improving our products and due to constant technical developments after the latest release date of the catalogue and/or individual datasheets. In order to always have the latest product and safety information make sure you visit our website (www.semperflex.com) regularly or contact one of our specialist dealers or a Semperit application engineer. All contracts with Semperflex are exclusively aut general information about the range, choice and safe use of our products can be found at our website (www.semperflex.com) and must be followed without exception. Important notice: Our catalogue and any individual datasheet have been prepared with great care in order to provide you with all the information you need. The information contained therein is based on the latest state-of-the-art industrial technology and many years of experience and testing: whenever indicated for a certain product, we also confirm conformity with the resistance requirements of the media listed in ISO TR 7620:2005(E). However, the individual conditions of storage, maintenance and use decisively affect the safe and durable use of each product. The quality and safety of our products as indicated in the cast logue or individual databets are therefore stirctly subject to the continuous observance of all specifications reparting resistance to chemicals and our cleaning procedures. We reject any liability for safety issues or other consequences due to improper product choice, maintenance or handling (e.g. squashing, rupturing, stretching or filling with non-approved media). Our products must not be used in airplanes or other aerial vehicles under any circumstance. Unless specified otherwise, all hoses are manufactured according to ENISO 1307:2008.



1

1