

915048 RAGNO N 40 BAR



PVC hose with polyester yarn reinforcement and PU adhesive intermediate layer for pressure spraying of insecticides, pesticides, liquids under pressure. * Double reinforcement - see SUPER RAGNO 80 BAR



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +60°C
23°F +140°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	WORKING PRESSURE 40°C	WORKING PRESSURE 60°C	BURSTING PRESSURE 23°C	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	bar	bar	m	
5/16	8	13.5	2.75	120	25	40	32	24	120	100	IN STOCK
3/8	10	16	3	160	30	40	32	24	120	100	IN STOCK
1/2	13*	21	4	290	50	40	32	24	120	100	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.

Double polyester yarn reinforcement, see SUPER RAGNO N 80 BAR CODE 915065 structure.