



Soft PVC hose with embedded galvanised steel spiral, for suction and delivery of food liquids.



SMOOTH SURFACES



FLEXIBILITY



ABRASION RESISTANCE



TEMPERATURE RANGE

-5°C +65°C
23°F +149°F



CHEMICAL RESISTANCE

PVC table



CRUSHING RESISTANCE



FOR FOOD

Suitable according to Reg. CE 1935/2004 and Reg. UE 10/2011 for contact with foodstuff that requires a simulating liquid type A B C, migration tests performed at 70°C for 2 hours.

Ø I.D.	Ø I.D.	Ø O.D.	TOTAL THICKNESS	WEIGHT	BENDING RADIUS	WORKING PRESSURE 1:3 23°C	BURSTING PRESSURE 23°C	VACUUM 23°C	SPIRAL PITCH	SPIRAL DIRECTION	Ø SPIRAL	COIL LENGTH	AVAILABILITY
inch	mm	mm	mm	g/m	mm	bar	bar	m h2o	mm		mm	m	
3/8	10	16	3	155	20	7	21	8.5	6.5	right	0.8	60	IN STOCK
	12	18	3	180	25	7	21	8.5	7	right	0.8	60	IN STOCK
	14	20	3	200	30	6	18	8.5	7.5	right	0.8	60	IN STOCK
5/8	16	22	3	225	35	6	18	8.5	7.5	right	0.8	60	IN STOCK
	18	24.5	3.25	280	40	6	18	8.5	8	right	1	60	IN STOCK
3/4	19	26	3.5	310	45	5	15	8.5	8	right	1	60	ON DEMAND
	20	27	3.5	340	50	5	15	8.5	8	right	1	60	IN STOCK
7/8	22	29	3.5	360	55	5	15	8.5	8.5	right	1	60	IN STOCK
1	25	33	4	510	60	5	15	8.5	13.5	right	1.4	60	IN STOCK
	30	39	4.5	600	70	4.5	13.5	8.5	13.5	right	1.4	60	IN STOCK
1 1/4	32	41	4.5	650	75	4.5	13.5	8.5	13.5	right	1.4	60	IN STOCK
	35	44	4.5	730	80	4	12	8.5	14.5	right	1.4	60	IN STOCK
1 1/2	38	47	4.5	800	90	4	12	8.5	15	right	1.6	30	IN STOCK
	40	49.5	4.75	870	95	3	9	8.5	15	right	1.6	30	IN STOCK
1 3/4	45	55	5	1100	110	3	9	8	15	right	1.8	30	IN STOCK
2	50	60	5	1200	125	3	9	8	16	right	1.8	30	IN STOCK
	55	66	5.5	1380	130	3	9	8	16.5	right	1.8	30	ON DEMAND
	60	72	6	1800	140	2.5	7.5	8	20	right	2.5	30	IN STOCK
2 1/2	63	75	6	1880	150	2.5	7.5	8	20	right	2.5	30	ON DEMAND
	70	83	6.5	2200	170	2	6	8	20	right	2.5	30	ON DEMAND
	75	89	7	2500	200	2	6	7	20	right	2.5	30	IN STOCK
3 1/2	80	94	7	2700	220	2	6	7	20	right	2.5	30	IN STOCK
	90	104	7	2900	260	2	6	7	20	right	2.5	30	ON DEMAND
	100	114	7	3250	300	2	6	7	19	right	2.5	30	IN STOCK

All technical specifications apply to a temperature of 23°C ± 2°C (ISO 291). - Tolerance on all specifications ± 5%.